




DEV9108-67

CG53-20S Replacement Cartridge

Drop-in Replacement Cartridge for Foodservice Applications



CG53-20S Replacement Cartridge: DEV9108-67

BENEFITS

- Submicron carbon block reduces extra fine particles and dirt from drinking water
- Effectively reduces contaminants such as Cryptosporidium and Giardia cysts
- Effectively reduces unwanted tastes, odor and chlorine
- High porosity design prevents the cartridge from plugging before its adsorption capacity is exhausted
- Improves the taste of beverages such as fountain drinks and coffee
- Phosphate reduces water-related equipment problems caused by scale build-up from dirt and dissolved minerals
- Helps keep equipment running at peak efficiency and keeps maintenance costs down
- Drop-in design fits most 20" bowls

INSTALLATION TIPS

- Install vertically so bowls hang down.
- Allow 2-1/2" clearance below the cartridge for easy cartridge replacement
- Make sure O-ring on bowl is sufficiently lubricated
- Always screw on bowls by hand; do not use a housing wrench

OPERATION TIPS

- Change cartridges on a regular 6 month preventative maintenance program
- Change cartridges when capacity is reached or when pressure decreases
- Always inspect O-ring; change and/or lubricate if necessary
- Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

- For foodservice applications requiring scale reduction
- Drop-in cartridge for taste, odor, sediment and cyst reduction
- Capacity: 20,000 gallons (75,700L)

CG53-20S Replacement Cartridge

SPECIFICATIONS

Overall Dimensions:
20"H x 2.87" Diameter


Service Flow Rate:
Maximum 4 gpm (15.1 Lpm)

Pressure Requirements:
30 - 125 psi (2.1 – 8.6 bar), non-shock

Temperature: 40 - 100°F (4.4 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

EVERPURE®

Worldwide Headquarters:
EVERPURE, LLC
1040 Muirfield Drive
Hanover Park, Illinois 60133
Toll Free (800) 323-7873
Tel (630) 307-3000
Fax (630) 307-3030
<http://www.everpure.com>

In Europe:
Pentair Water Belgium B.V./B.A.
Industriepark Wolfstee
Toekomstlaan 30
B- 2200 Herentals
BELGIUM
TEL: +32.(0).14.283.500
FAX: +32.(0).14.283.505

In Japan:
Hashimoto MN Bldg. 7F
3-25-1 Hashimoto Sagamihara-Shi
Kanagawa 229-1103
JAPAN
TEL: 81.(0)42.775.3011
FAX: 81.(0)42.775.3015